Printing date 01/08/2013

Reviewed on 01/08/2013



### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: #191 Black
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation stamp pad ink
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Noris-Color GmbH

Ziegelhuettener Str.1

Germany-95326 Kulmbach

Phone: +49(0) 9221 - 92 00 0

Fax: +49(0) 9221 - 92 00 90

E-mail: info@noris-color.de

- · Information department: Laboratory/product safety
- · Emergency telephone number: see "manufacturer/supplier"

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC
- · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

R 10 Flammable.

R 33 Danger of cumulative effects.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

- · Hazard-determining components of labelling: parfum (only for industrial use)
- · Risk phrases:
- 10 Flammable.
- 33 Danger of cumulative effects.
- · Safety phrases:
- 2 Keep out of the reach of children.
- 24 Avoid contact with skin.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- · Classification system:
- · NFPA ratings (scale 0 4)

Health = 0

Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = 0

Fire = 2

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 2)

Printing date 01/08/2013

Reviewed on 01/08/2013

Trade name: #191 Black

· Personal Protection letter: B Safety Glasses & Gloves

(Contd. of page 1)

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
Dipropylenglykolmonomethylether, Isomerengem.	25-50%
1,2-Propylenglycol-1-monomethylether	25-50%
Butyloxidhydrat	2.5-10%
parfum (only for industrial use)	< 2.5%

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Printing date 01/08/2013

Reviewed on 01/08/2013

Trade name: #191 Black

See Section 13 for disposal information.

(Contd. of page 2)

## 7 Handling and storage

- · Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### Dipropylenglykolmonomethylether, Isomerengem.

PEL 600 mg/m³, 100 ppm

Skin

REL | Short-term value: 900 mg/m³, 150 ppm

Long-term value: 600 mg/m³, 100 ppm

Skin

TLV Short-term value: 909 mg/m³, 150 ppm

Long-term value: 606 mg/m³, 100 ppm

Skin

#### 1,2-Propylenglycol-1-monomethylether

REL Short-term value: 540 mg/m³, 150 ppm

Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

#### Butyloxidhydrat

PEL 300 mg/m³, 100 ppm

REL Short-term value: C 150 mg/m³, C 50 ppm

Ski.

TLV 61 mg/m<sup>3</sup>, 20 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

(Contd. on page 4)

Printing date 01/08/2013

Reviewed on 01/08/2013

Trade name: #191 Black

(Contd. of page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Not suitable are gloves made of the following materials: Natural rubber, NR
- · Eye protection:

Tightly sealed goggles recommended during refiling/handling larger quantities.

Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance:	rlJ
Form: Color:	Fluid
Cotor: Odor:	According to product specification Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	116°C (241 °F)
Flash point:	54°C (129 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	270°C (518 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapmixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	14.0 Vol %
Vapor pressure at 20°C (68 °F):	12 hPa (9 mm Hg)
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	76.0 %
Water:	0.0 %

Printing date 01/08/2013

Reviewed on 01/08/2013

Trade name: #191 Black

	(Contd. of	page 4)
VOC content:	76.0 %	
Solids content:	24.0 %	
· Other information	No further relevant information available.	

#### 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 6)

Printing date 01/08/2013

Reviewed on 01/08/2013

(Contd. of page 5)

Trade name: #191 Black

· Waste disposal key: recommendation: 080111 (waste containing organic solvents)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name DOT, IMDG, IATA ADR	PAINT 1263 PAINT	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids.	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	III	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler): EMS Number:	30 E E S E	
EMS Number:	F-E,S-E	

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances): no
- · Section 313 (Specific toxic chemical listings): no
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: Noris-Color GmbH; laboratory/product safety; info@noris-color.de